



Contact factory for other dimensional, temperature, load, or axial travel, requirements. If lateral load is greater than 20% of vertical load, contact factory.

The load ratings represent average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. Dimensions and ratings are subject to change without notice.

Note: For higher load ratings, see: B3300 - For greater axial travel, see: B4200 - For lateral travel, see: B5200

Pipe Size	Vert. Load	Insul. Thk. = 1"			Insul. Thk. = 1-1/2"			Insul. Thk. = 2"			Insul. Thk. = 2-1/2"			Insul. Thk. = 3"			Insul. Thk. = 4"			Insul. Thk. = 5"		
		B	C	E	B	C	E	B	C	E	B	C	E	B	C	E	B	C	E	B	C	E
1/2	400	4	6	3.25	4	6.5	4.375	4	7	5.375	4	8.5	7	6	9	8	6	11	10	8	12.5	12.125
3/4	500	4	6	3.25	4	6.5	4.375	4	7	5.375	4	8.5	7	6	9	8	6	11	10	8	12.5	12.25
1	650	4	6.5	4	4	7	5	4	7.5	6.062	4	8.5	7.125	6	9	8.125	6	11	10.125	8	12.5	12.25
1 1/2	950	4	6.5	4.5	4	7	5.5	4	8.5	7.125	4	9	8.125	6	10	9.125	6	12	11.25	8	13.5	13.25
2	1100	4	7	5	4	7.5	6.1875	4	8.5	7.125	4	9	8.125	6	10	9.125	6	12	11.25	8	13.5	13.25
2 1/2	1350	4	7	5.5	4	8.5	7.125	4	9	8.125	4	10	9.125	6	11	10.125	6	12.5	12.25	8	14	14.5
3	1600	4	7.5	6.187	4	8.5	7.125	4	9	8.125	4	10	9.125	6	11	10.125	6	12.5	12.375	8	14	14.625
4	2500	4	8.5	7.25	4	9	8.25	4	10	9.25	4	11	10.25	6	12	11.375	6	13.5	13.375	8	15	15.625
5	3100	4	10	8.5	4	11	9.5	4	12	10.5	4	13	11.625	6	13.5	12.625	6	15	14.875	8	16.5	16.875
6	3800	4	11	9.5	4	12	10.5	4	13	11.625	4	13.5	12.625	6	14.5	13.625	6	16	15.875	8	17.5	17.875
8	5100	4	13.5	11.625	4	14	12.625	4	15	13.625	4	15.5	14.875	6	16.5	15.875	6	18	18.125	8	19	20.125
10	6000	4	15	13.875	4	15.5	15.125	4	16.5	16.125	4	17	17.125	6	18	18.125	6	19	20.125	8	20.5	22.125
12	6600	4	17	16.125	4	17.5	17.125	4	18.5	18.125	4	19	19.125	6	19.5	20.125	6	21	22.125	8	22.5	24.125
14	7500	4	17.5	17.125	4	18.5	18.125	4	19	19.125	4	19.5	20.125	6	20.5	21.125	6	22	23.125	8	23	25.125
16	8700	4	20.5	19.375	4	21	20.375	4	22	21.375	4	22.5	22.375	6	23.5	23.375	6	24.5	25.375	8	26	27.375
18	9600	4	22	21.375	4	22.5	22.375	4	23.5	23.375	4	24	24.375	6	24.5	25.375	6	26	27.375	8	27.5	29.375
20	10200	4	23.5	23.375	4	24	24.375	4	24.5	25.375	4	25.5	26.375	6	26	27.375	6	27.5	29.375	8	29	31.375
24	10800	4	26	27.375	4	27	28.375	4	27.5	29.375	4	28.5	30.375	6	29	31.375	6	30.5	33.375	8	32	35.375
30	14100	4	32.5	33.625	4	33	34.625	4	34	35.625	4	34.5	36.625	6	35	37.625	6	36.5	39.625	8	38	41.625
36	16500	4	36.5	40.125	4	37.5	41.125	4	38	42.125	4	38.5	43.125	6	39.5	44.125	6	41	46.125	8	42.5	48.125
42	18600	4	41	46.125	4	41.5	47.125	4	42.5	48.125	4	43	49.125	6	43.5	50.125	6	45	52.125	8	46.5	54.125

**Application:**

- Model B3200 is designed for use on:
- Hot Water
  - Cold Water
  - Dual Temperature
  - Vacuum
  - Steam
  - Chilled Water
  - Gas
  - Air

Intended for installation on:

- Flat Surfaces

**Temperature Range: +40°F to +1200°F**  
 Note: Up to 1700° F available upon request.

**Features:**

- All pipe sizes
- Easy Installation
- Eliminates welding to pipe
- Overlapping galvanized sheet metal jacket
- Insulating structural inserts for load transfer
- Stainless steel to UHMW polyethylene slide
- Other I.D.'s and/or O.D.'s available on request
- Factory mounted polyethylene slide pad on steel mounting plate

Performance Test Results on File:  
 Available upon request.

**Material Data:**

- **B3200:** Applicable PSI spec. doc.: No. 209.
- **Insulation:** Calcium Silicate asbestos-free, treated with water repellant.
- **Jackets:** Galvanized Steel ASTM A-527.
- **Glue:** Industrial contact adhesive
- **Structural Inserts:** High-density calcium silicate asbestos free, treated with water repellant.
- **Steel Straps/Base:** Carbon Steel ASTM A-36.
- **Fasteners:** ASTM A-307 plated.
- **Slide Pad:** UHMW Polyethylene (Teflon Optional).
- **Coating:** Primer coated or hot dipped galvanized. Other coatings available upon request.

**Formal Submittal Sheets available.**