



The load ratings represent average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. Dimensions and ratings are subject to change without notice. Contact factory for current information.

Note: For higher load ratings, see: D3100

Pipe Size	(a) load lbs.	A	B	C	D	Insul. Thk 1"		Insul. Thk 2"		Insul. Thk 3"		Insul. Thk 4"		Insul. Thk 5"	
						E	F	E	F	E	F	E	F	E	F
						1	285	3/16x2	0.375	0.675	0.75	2.81	6	3.84	6
1 1/2	320	3/16x2	0.375	0.675	0.75	3.06	6	4.38	6	5.38	6	6.44	6	7.44	6
2	320	3/16x2	0.375	0.675	0.75	3.31	6	4.38	6	5.38	6	6.44	6	7.44	6
2 1/2	540	1/4x2	0.375	0.675	0.75	3.69	6	5	6	6	6	7.06	6	8.19	6
3	540	1/4x2	0.375	0.675	0.75	3.97	6	5	6	6	6	7.06	6	8.19	6
4	770	1/4x3	0.5	0.84	0.75	4.63	6	5.63	6	6.69	6	7.69	6	8.81	6
5	1125	3/8x3	0.5	0.84	0.75	5.38	6	6.38	6	7.44	6	8.56	6	9.56	6
6	1430	3/8x3	0.625	1.05	0.75	6	6	7.06	6	8.06	6	9.18	6	10.19	6
8	1805	1/2x3	0.625	1.05	0.75	7.31	6	8.31	6	9.44	6	10.44	6	11.44	6
10	2310	1/2x3	0.75	1.05	0.75	8.44	6	9.56	6	10.56	6	11.56	6	12.56	6
12	2705	5/8x3	0.75	1.05	0.75	9.69	6	10.69	6	11.69	6	12.69	6	13.69	6
14	2705	5/8x3	0.75	1.05	0.75	10.19	6	11.19	6	12.18	6	13.19	6	14.19	6
16	3035	5/8x3	0.875	1.315	1	11.31	6	12.31	6	13.31	6	14.31	6	15.31	6
18	3750	3/4x3	0.875	1.315	1	12.56	6	13.56	6	14.56	6	15.56	6	16.56	6
20	3855	3/4x3	1	1.315	1	13.69	6	14.69	6	15.69	6	16.69	6	17.69	6
24	4935	1x3	1	1.315	1	16.19	6	17.19	6	18.19	6	19.18	6	20.19	6
30	5295	1x3	1.25	1.66	1.25	19.44	6	20.44	6	21.44	6	22.44	6	23.44	6
36	7855	1x6	1.25	1.66	1.25	22.44	9	23.44	9	24.44	9	25.44	9	26.44	9
42	7970	1x6	1.25	1.66	1.25	25.44	9	26.44	9	27.44	9	28.44	9	29.44	9

TABLE I

<p>Application:</p> <p>Model D3000 is designed for use on:</p> <ul style="list-style-type: none"> · Hot Water · Vacuum · Gas · Cold Water · Steam · Air · Dual Temperature · Chilled Water <p>Intended to be hung from threaded rod</p> <p>Temperature Range: +40°F to +1200°F</p>	<p>Features:</p> <ul style="list-style-type: none"> · Compact · Easy installation · Eliminates welding to pipe · Copper tubing sizes and pipe sizes · Overlapping galvanized sheet metal jacket · Minimizes heat-loss and/or condensation · Other I.D.'s and/or O.D.'s available on request <p>Performance Test Results on File: Available upon request.</p>	<p>Material Data:</p> <ul style="list-style-type: none"> · D3000: Applicable PSI specification document: No. 209. · Insulation: Calcium Silicate asbestos-free, treated with water repellent. · Jackets: Galvanized Steel ASTM A-527. · Glue: Industrial contact adhesive · Structural Inserts: High-density calcium silicate asbestos free, treated with water repellent. · Steel Straps: Carbon Steel ASTM A-36. · Fasteners: ASTM A-307 plated. · Coating: Primer coated or hot dipped galvanized. Other coatings available upon request. <p>Formal Submittal Sheets available.</p>
---	--	--