



Pipe Size	Maximum Lateral Load - Lbs
3/4	50
1	50
1-1/4	50
1-1/2	50
2	50
2-1/2	50
3	50
3-1/2	50
4	50
5	50
6	50
8	50
10	50
12	50

TABLE I

Insulation Thicknesses
0
1/2
3/4
1
1-1/2
2
2-1/2
3
3-1/2
4

TABLE II

Contact factory for pipe sizes or insulation thicknesses not shown.

Note: For neoprene lined clamps, see: G1200; For bolt-on clamps, see: G2000; For U-bolts, see: G3000

Insulation and Framing Channel sold separately.

<p><b>Application:</b></p> <p>Model G1000 is designed for use on:</p> <ul style="list-style-type: none"> <li>· Hot Water</li> <li>· Cold Water</li> <li>· Chilled Water</li> <li>· Dual Temperature</li> <li>· Steam</li> <li>· Air</li> <li>· Gas</li> <li>· Vacuum</li> </ul> <p>Intended for installation on:</p> <ul style="list-style-type: none"> <li>· Standard 1-5/8" width Framing Channels</li> </ul>	<p><b>Features:</b></p> <ul style="list-style-type: none"> <li>· Easy installation</li> <li>· Rugged</li> <li>· Fits standard 1-5/8" width framing channel</li> <li>· Sized to clamp on O.D. of bare pipe</li> <li>· Sized to clamp on O.D. of insulated pipe support models A1000 through A7400</li> <li>· Complete with top bolt and nut</li> <li>· Other sizes available on request</li> </ul>	<p><b>Material Data:</b></p> <ul style="list-style-type: none"> <li>· <b>G1000:</b> Applicable PSI specification document: No. 208.</li> <li>· <b>Steel:</b> Galvanized Steel 11 ga. X 1-1/4 wide ASTM A-527</li> <li>· <b>Fasteners:</b> ASTM A-307 Plated.</li> </ul> <p><b>Formal Submittal Sheets available.</b></p>
---	---	--