



Pipe Size	Maximum Lateral Load - Lbs
3/4	200
1	200
1-1/4	200
1-1/2	200
2	400
2-1/2	400
3	400
3-1/2	400
4	400
5	400
6	400
8	400
10	400
12	400

TABLE I

Insulation Thicknesses
0
1/2
3/4
1
1-1/2
2
2-1/2
3
3-1/2
4

TABLE II

Contact factory for pipe sizes or insulation thicknesses not shown.

Note: For neoprene lined straps, see: G2200; For pipe/shield clamps, see: G1000; For U-bolts, see: G3000

Insulation and Framing Channel sold separately.

<p><b>Application:</b></p> <p>Model G2000 is designed for use on:</p> <ul style="list-style-type: none"> <li>· Hot Water</li> <li>· Cold Water</li> <li>· Chilled Water</li> <li>· Dual Temperature</li> <li>· Steam</li> <li>· Air</li> <li>· Gas</li> <li>· Vacuum</li> </ul> <p>Intended for installation on:</p> <ul style="list-style-type: none"> <li>· Standard 1-5/8" width Framing Channels</li> </ul>	<p><b>Features:</b></p> <ul style="list-style-type: none"> <li>· Easy installation</li> <li>· Rugged</li> <li>· Bolts to standard 1-5/8" width framing channel</li> <li>· Sized to clamp on O.D. of bare pipe</li> <li>· Sized to provide approximately 1/16" radial clearance around O.D. of insulated pipe support models A1000 through A7400</li> <li>· Complete with top bolt and nut plus two (2) tie down bolts and channel nuts with springs</li> <li>· Other sizes available on request</li> </ul>	<p><b>Material Data:</b></p> <ul style="list-style-type: none"> <li>· <b>G2000:</b> Applicable PSI specification document: No. 208.</li> <li>· <b>Steel:</b> ASTM A36 1/4 X 1-1/2</li> <li>· <b>Fasteners:</b> ASTM A-307 Plated.</li> <li>· <b>Coating:</b> Primer coating or hot dipped galvanized. Other coatings available upon request.</li> </ul> <p><b>Formal Submittal Sheets available.</b></p>
---	--	--