



Contact factory for other dimensional, temperature, load, or axial travel, requirements. If lateral load is greater than 50% of actual vertical load, contact factory.

The load ratings represent average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. Dimensions and ratings are subject to change without notice.

Note: For higher load ratings, see: B8200 - For lateral travel, see: B6100

Pipe Size	Vert. Load	Insul. Thk. = 1"			Insul. Thk. = 1-1/2"			Insul. Thk. = 2"			Insul. Thk. = 2-1/2"			Insul. Thk. = 3"			Insul. Thk. = 4"			Insul. Thk. = 5"		
		B	C	E	B	C	E	B	C	E	B	C	E	B	C	E	B	C	E	B	C	E
1/2	250	4	5	3.25	4	5.5	4.375	4	6	5.375	4	7.5	7	6	8	8	6	10	10	8	11.5	12.125
3/4	310	4	5	3.25	4	5.5	4.375	4	6	5.375	4	7.5	7	6	8	8	6	10	10	8	11.5	12.25
1	400	4	5.5	3.875	4	6	5	4	6.5	6.062	4	7.5	7	6	8	8	6	10	10	8	11.5	12.25
1 1/2	580	4	5.5	4.5	4	6	5	4	7.5	7.125	4	8	8.125	6	9	9.125	6	11	11.25	8	12.5	13.25
2	670	4	6	5	4	6.5	6.0625	4	7.5	7.125	4	8	8.125	6	9	9.125	6	11	11.25	8	12.5	13.25
2 1/2	820	4	6.5	5.5	4	8	7.125	4	8.5	8.125	4	9.5	9.125	6	10.5	10.125	6	12	12.25	8	13.5	14.5
3	950	4	7	6.187	4	8	7.125	4	8.5	8.125	4	9.5	9.125	6	10.5	10.125	6	12	12.375	8	13.5	14.625
4	1500	4	8.5	7.25	4	9	8.25	4	10	9.25	4	11	10.25	6	12	11.375	6	13.5	13.375	8	15	15.625
5	1880	4	9.5	8.5	4	10.5	9.5	4	11.5	10.5	4	12.5	11.625	6	13	12.625	6	14.5	14.875	8	16	16.875
6	2280	4	10	9.5	4	11	10.5	4	12	11.625	4	12.5	12.625	6	13.5	13.625	6	15	15.875	8	16.5	17.875
8	3000	4	13	11.625	4	13.5	12.625	4	14.5	13.625	6	15	14.875	6	16	15.875	6	17.5	18.125	8	18.5	20.125
10	3600	4	14.5	13.875	4	15	15.125	4	16	16.125	6	16.5	17.125	6	17.5	18.125	6	18.5	20.125	8	20	22.125
12	3900	4	16.5	16.125	4	17	17.125	4	18	18.125	6	18.5	19.125	6	19	20.125	6	20.5	22.125	8	22	24.125
14	4500	4	17.5	17.125	4	18.5	18.125	4	19	19.125	6	19.5	20.125	6	20.5	21.125	6	22	23.125	8	23	25.125
16	5200	4	19	19.375	4	19.5	20.375	6	20.5	21.375	6	21	22.375	6	22	23.375	8	23	25.375	8	24.5	27.375
18	5700	4	21	21.375	4	21.5	22.375	6	22.5	23.375	6	23	24.375	6	23.5	25.375	8	25	27.375	8	26.5	29.375
20	6100	4	22.5	23.375	4	23	24.375	6	23.5	25.375	6	24.5	26.375	6	25	27.375	8	26.5	29.375	8	28	31.375
24	6400	4	25.5	27.375	4	26.5	28.375	6	27	29.375	6	28	30.375	6	28.5	31.375	8	30	33.375	8	31.5	35.375
30	8400	4	31.5	33.625	6	32	34.625	6	33	35.625	6	33.5	36.625	6	34	37.625	8	35.5	39.625	8	37	41.625
36	9800	4	36	40.125	6	37	41.125	6	37.5	42.125	6	38	43.125	6	39	44.125	8	40.5	46.125	8	42	48.125
42	11100	4	41.5	46.125	6	42	47.125	6	43	48.125	6	43.5	49.125	6	44	50.125	8	45.5	52.125	8	47	54.125

**Application:**

- Model B8100 is designed for use on:
  - Hot Water
  - Vacuum
  - Gas
  - Cold Water
  - Steam
  - Air
  - Dual Temperature
  - Chilled Water

Intended for installation on:  
Flat Surfaces

Temperature Range: +40°F to +1200°F  
Note: Up to 1700°F available upon request.

**Features:**

- All pipe sizes
- Easy installation
- Eliminates welding to pipe
- Overlapping galvanized sheet metal jacket
- Insulating structural inserts for load transfer
- Stainless steel to UHMW polyethylene slide
- Other I.D.'s and O.D.'s available on request
- Factory mounted polyethylene slide pad on steel mounting plate

Performance Test Results on File:  
Available upon request.

**Material Data:**

- B8100: Applicable PSI spec. doc.: No. 209.
- Insulation: Calcium Silicate asbestos-free, treated with water repellent.
- Jackets: Galvanized Steel ASTM A-527.
- Gluers: Industrial contact adhesive
- Structural Inserts: High-density calcium silicate asbestos free, treated with water repellent.
- Steel Straps/Bases: Carbon Steel ASTM A-36.
- Fasteners: ASTM A-307 plated.
- Slide Pad: UHMW Polyethylene (Teflon Optional).
- Coating: Primer coated or hot dipped galvanized. Other coatings available upon request.

For Material Sheet available.