



Contact factory for other dimensional, temperature, load, or axial travel, requirements. If lateral load is greater than 50% of actual vertical load, contact factory.

The load ratings represent average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. Dimensions and ratings are subject to change without notice.

Note: For lateral travel, see: B6300

Pipe Size	Vert. Load	Insul. Thk. = 1"			Insul. Thk. = 1-1/2"			Insul. Thk. = 2"			Insul. Thk. = 2-1/2"			Insul. Thk. = 3"			Insul. Thk. = 4"			Insul. Thk. = 5"		
		B	C	E	B	C	E	B	C	E	B	C	E	B	C	E	B	C	E	B	C	E
1/2	500	4	5	3.375	4	5.5	4.5	4	6	5.5	4	7.5	7.125	6	8	8.125	6	10	10.125	8	11.5	12.25
3/4	620	4	5	3.375	4	5.5	4.5	4	6	5.5	4	7.5	7.125	6	8	8.125	6	10	10.125	8	11.5	12.25
1	800	4	5.5	4	4	6	5	4	6.5	6.062	4	7.5	7.125	6	8	8.125	6	10	10.125	8	11.5	12.25
1 1/2	1160	4	6	4.5	4	6.5	5.5	4	8	7.125	4	8.5	8.125	6	9.5	9.125	6	11.5	11.25	8	13	13.25
2	1340	4	7	5	4	7.5	6.0625	4	8.5	7.125	4	9	8.125	6	10	9.125	6	12	11.25	8	13.5	13.25
2 1/2	1640	4	7	5.5	4	8.5	7.125	4	9	8.125	4	10	9.125	6	11	10.125	6	12.5	12.375	8	14	14.625
3	1900	4	8	6.187	4	9	7.125	4	9.5	8.125	4	10.5	9.125	6	11.5	10.125	6	13	12.375	8	14.5	14.625
4	3000	4	10	7.25	4	10.5	8.25	4	11.5	9.25	4	12.5	10.25	6	13.5	11.375	6	15	13.375	8	16.5	15.625
5	3760	4	13	8.5	4	13.5	9.5	4	15	10.5	4	16.5	11.625	6	17.5	12.625	6	19.5	14.875	8	21	16.875
6	4560	4	13	9.5	4	14.5	10.5	4	16	11.625	4	17	12.625	6	18.5	13.625	6	19.5	15.875	8	21.5	17.875
8	6000	4	17	11.625	4	18	12.625	4	19.5	13.625	6	20	14.875	6	21	15.875	6	22.5	18.125	8	24	20.125
10	7200	4	20	13.875	4	20.5	15.125	4	21.5	16.125	6	22	17.125	6	23	18.125	6	24.5	20.125	8	26.5	22.125
12	7800	4	21.5	16.125	4	22	17.125	4	23	18.125	6	24	19.125	6	24.5	20.125	6	26.5	22.125	8	28	24.375
14	9000	4	22.5	17.125	4	23.5	18.125	4	24.5	19.125	6	25	20.125	6	26	21.125	6	28	23.375	8	29	25.375
16	10400	4	24.5	19.375	4	25	20.375	6	26	21.375	6	27	22.375	6	28	23.375	8	29	25.375	8	30	27.375
18	11400	4	26.5	21.375	4	27.5	22.375	6	28.5	23.375	6	29	24.375	6	29.5	25.375	8	30.5	27.375	8	32	29.375
20	12200	4	29	23.375	4	29.5	24.375	6	30	25.375	6	30.5	26.375	6	31	27.375	8	32.5	29.375	8	34	31.375
24	12800	4	31.5	27.375	4	32.5	28.375	6	33	29.375	6	33.5	30.375	6	34.5	31.375	8	36	33.625	8	37.5	35.625
30	16800	4	37.5	33.625	6	38.5	34.625	6	39	35.625	6	40	37.125	6	41	38.125	8	42.5	40.125	8	44	42.125
36	19600	4	44	40.125	6	44.5	41.125	6	45.5	42.125	6	46.5	43.125	6	47	44.125	8	48.5	46.125	8	50.5	48.125
42	22200	4	50	46.125	6	51	47.125	6	52	48.125	6	52.5	49.125	6	53.5	50.125	8	55	52.125	8	56.5	54.125

**Application:**

Model B8300 is designed for use on:

- Hot Water
- Cold Water
- Dual Temperature
- Vacuum
- Steam
- Chilled Water
- Gas
- Air

Intended for installation on:

- Flat Surfaces

Temperature Range: +40°F to +120°F

Note: Up to 1700°F available upon request.

**Features:**

- All pipe sizes
- Easy installation
- Eliminates welding to pipe
- Overlapping galvanized sheet metal jacket
- Insulating structural inserts for load transfer
- Stainless steel to UHMW polyethylene slide
- Other I.D.'s and O.D.'s available on request
- Factory mounted polyethylene slide pad on steel mounting plate

Performance Test Results on File:  
Available upon request.

**Material Data:**

- B8300: Applicable PS I spec. doc.: N o. 2 09.
- Insulation: Calcium Silicate abestos-free, treated with water repellent.
- Jackets: Galvanized Steel ASTM A-527.
- Glue: Industrial contact adhesive
- Structural Inserts: High-density calcium silicate abestos free, treated with water repellent.
- Steel Straps/Bases: Carbon Steel ASTM A-36.
- Fasteners: ASTM A-307 plated.
- Slide Pad: UHMW Polyethylene (Teflon Optional).
- Coating: Primer coated or hot dipped galvanized. Other coatings available upon request.

For Material Submittal Sheets available.